

# Christie FHD461-X

Broadcast sets  
Control rooms  
Corporate spaces  
Higher education

Hospitality  
Museums  
Retail environments  
Stadiums



## Best-of-class ultra-narrow bezel LCD display

With the tightest seams, best image quality and slimmest profile in its category, the Christie® FHD461-X 46" HD LCD flat panel is a true class leader. Featuring high pixel density, 1.07 billion colors and a 4000:1 contrast ratio, the ultra-narrow bezel Christie FHD461-X produces vivid, crisp images on a near-seamless tiled video wall display.

Competitively priced and offering low operating costs, the Christie FHD461-X is ENERGY STAR® qualified and features a long-lasting LED backlight to provide optimal 24/7 performance.

Christie's pro AV expertise makes it easy to bring your video wall to life – with versatile multi-touch interactive technology, mounts and structural supports as well as the best range of image processors, media servers and controllers on the market. And backed by our industry-renowned service and technical support, you'll have peace of mind.

Impress with beautiful visuals, save on space and money, and head to the top of the class with the Christie FHD461-X.

Christie FHD461-X Major competitors\*



3.0"  
(78mm)

3.4 - 4.6"  
86 - 117mm



1.07 billion

16.7 million



4000:1

3500:1

\*Based on competitive comparison July 2013


**CHRISTIE®**

FHD461-X			
<b>Display</b>	screen size (diagonal)	• 46" (1168.4mm)	
	native resolution	• 1920 x 1080 (16:9)	
	technology	• Commercial-grade LCD	
	backlight	• Direct LED	
	LED lifespan	• 50,000 hrs (50% brightness)	
	display orientation	• Landscape or portrait	
	pixel pitch	• 0.02 x 0.02" (0.53 x 0.53mm)	
	nominal bezel size	• 0.13" (3.4mm) (top/left) • 0.08" (2.0mm) (bottom/right)	
	brightness	• 700 nits (cd/m <sup>2</sup> ) maximum • 500 nits (cd/m <sup>2</sup> ) typical	
	contrast ratio (full field)	• 4000:1	
	viewing angle (CR 10:1)	• 178° h/v	
	refresh rate	• 50/60Hz	
	response time	• 6.5 ms	
	color space (CIE 1931)	• 72%	
display colors	• 1.07 billion		
<b>Signal</b>	inputs	• HDMI (HDCP) x2 • DVI (HDCP) • DisplayPort • VGA • Component • S-Video • Composite • Audio L/R • Audio 3.5mm • Infrared extender 3.5mm	
	outputs	• DVI (HDCP) • VGA • Audio 3.5mm	
<b>Control</b>	inputs	• RS-232 • RS-485	
	outputs	• RS-485	
<b>Power</b>	input rating	• 100-240 VAC @ 50/60Hz; 2A	
	power consumption	• 170W maximum • 105W typical • ≤0.5W standby	
	ENERGY STAR®	• 6.0	
<b>Environmental</b>	operating temperature	• 41°-104°F (5°-40°C)	
	operating humidity	• 20-90% non-condensing	
	storage temperature	• -4°-41°F (-20°-60°C)	
<b>Physical</b>	Dimensions (WxHxD)	Weight	
	panel only	• 40.31 x 22.77 x 3.08" (1023.8 x 578.4 x 78.2mm)	• 51lbs (23kg)
	panel with quick access mount <sup>1</sup>	• 40.31 x 22.77 x 6.15-6.90" (1023.8 x 578.4 x 156.2-175.2mm)	• 99lbs (45kg)
	panel with thin profile mount <sup>1</sup>	• 40.31 x 22.77 x 3.78" (1023.8 x 578.4 x 95.7mm)	• 64lbs (29kg)
	panel mount locations	• VESA standard (WxH) 23.62 x 15.75" (600 x 400mm)	
<b>Runtime</b>	• Designed for 24/7 operation <sup>2</sup> , featuring a reliable power supply and cooling system		
<b>Features</b>	<ul style="list-style-type: none"> <li>• Commercial-grade LCD • Anti-glare coating • Full HD resolution • Landscape or portrait orientation • Front-accessible mount • Stackable frames and pedestals • Advanced cooling design • High energy efficiency with ≤0.5W standby • Plug and Play (DDC2B)</li> <li>• Bezel compensation option • Image Retention Frame Motion (IRFM) mode • Auto Scan source selection • Aspect-ratio control • Zoom • Picture-in-Picture (PiP) • Advanced image settings</li> <li>• Configurable power on delay • Sleep timer • Single DVI input can be shared by up to 3x3 panels</li> <li>• Control up to 25 panels through single RS-232 and Video Wall Toolbox software on a remote PC</li> <li>• Auto setup for single-input video wall • Control each panel with on-screen display (OSD) using infrared (IR) remote control</li> </ul>		
<b>Accessories</b>	<ul style="list-style-type: none"> <li>• Panel ships with remote control, IR extender, DVI cable, Ethernet cable (RS-485) and RS-232 cable</li> <li>• Regional power cord available separately • Quick access wall mounts: ML10 for landscape, MP10 for portrait, spacer kits available • Thin wall mount available from third party</li> </ul>		
<b>Warranty</b>	<ul style="list-style-type: none"> <li>• Three years parts and labor limited warranty</li> <li>• Contact an authorized Christie representative for full details of our limited warranty</li> </ul>		


<sup>1</sup> Christie offers a quick access mount for easy servicing and alignment. The above dimensions and weight with thin profile mount are based on Peerless DS-VW650. If using a third party mount, please check with the supplier for exact specifications.

<sup>2</sup> Avoid static images for extended periods. Refer to the user manual for additional runtime guidance.


### Front of panel




### Minimal bezels




### Back of panel



### Quick access mount



### Thin profile mount<sup>1</sup>



▲ Complies with U.S. ADA regulations for installed depth under 4"

### Corporate offices

Christie Digital Systems USA, Inc.  
USA – Cypress  
ph: 714 236 8610

Christie Digital Systems Canada Inc.  
Canada – Kitchener  
ph: 519 744 8005

### Worldwide offices

Australia  
ph: +61 (0) 7 3844 9514

Brazil  
ph: +55 (11) 2548 4753

China (Beijing)  
ph: +86 10 6561 0240

China (Shanghai)  
ph: +86 21 6278 7708

Eastern Europe and  
Russian Federation  
ph: +36 (0) 1 47 48 100

France  
ph: +33 (0) 1 41 21 44 04

Germany  
ph: +49 2161 664540

India  
ph: +91 (080) 6708 9999

Japan (Tokyo)  
ph: 81 3 3599 7481

Korea (Seoul)  
ph: +82 2 702 1601

Republic of South Africa  
ph: +27 (0)11 510 0094

Singapore  
ph: +65 6877 8737

Spain  
ph: +34 91 633 9990

United Arab Emirates  
ph: +971 4 3206688

United Kingdom  
ph: +44 (0) 118 977 8000

Independent sales  
consultant offices

Italy  
ph: +39 (0) 2 9902 1161



For the most current specification information, please visit [www.christiedigital.com](http://www.christiedigital.com)